

# SPECTRUM-CONSERVATION TECHNIQUES FOR FIXED MICROWAVE SYSTEMS

ROBERT L. HINKLE  
ANDREW FARRAR



U.S. DEPARTMENT OF COMMERCE  
Robert A. Mosbacher, Secretary

Alfred C. Sikes, Assistant Secretary  
for Communications and Information

MAY 1989



## ABSTRACT

Since the spectrum is a limited natural resource, the spectrum management community has a major interest in identifying spectrum conservation techniques that will provide more efficient spectrum utilization. Advances in new technology for fixed microwave systems in antennas, modulation schemes and signal processing techniques offer increased efficiency in spectrum utilization. This report analyzes the spectrum conserving properties of the various new technologies for fixed microwave systems applying the concepts in CCIR Report 662-2, and was defined as the spectrum conservation factor (SCF). The report concludes that the SCF technique is an effective indicator of the spectrum conserving properties of technologies which can be used to develop new spectrum standards.

## KEYWORDS

Spectrum Efficiency  
Spectrum Conservation Factor (SCF)  
Fixed Microwave System  
7125-8500 MHz Band



## TABLE OF CONTENTS

Subsection	Page
SECTION 1	
INTRODUCTION	
BACKGROUND . . . . .	1-1
OBJECTIVE . . . . .	1-3
APPROACH . . . . .	1-3
SECTION 2	
CONCLUSIONS AND RECOMMENDATIONS	
INTRODUCTION . . . . .	2-1
GENERAL CONCLUSIONS . . . . .	2-2
SPECIFIC CONCLUSIONS . . . . .	2-2
Antennas . . . . .	2-2
Modulation . . . . .	2-3
Signal Processing . . . . .	2-3
RF Filters . . . . .	2-4
RECOMMENDATIONS . . . . .	2-4
SECTION 3	
ANALYSIS FOR SPECTRUM CONSERVATION TECHNIQUES	
INTRODUCTION . . . . .	3-1
ANALYSIS APPROACH . . . . .	3-1
MICROWAVE REFERENCE SYSEM CHARACTERISTICS . . . . .	3-3

**TABLE OF CONTENTS**  
**(Continued)**

Subsection	Page
SECTION 3	
(Continued)	
ANTENNAS . . . . .	3-3
Antenna Pattern Characteristics . . . . .	3-3
Spectrum Conservation Factor . . . . .	3-6
Antenna Cost . . . . .	3-9
MODULATION . . . . .	3-11
Digital Modulation . . . . .	3-11
Digital System Occupied Bandwidth . . . . .	3-12
Digital System Transmitter Output Power . . . . .	3-13
Analog Modulation . . . . .	3-14
Analog System Occupied Bandwidth . . . . .	3-15
Analog System Transmitter Output Power . . . . .	3-15
Maximum Permissible Interference Level . . . . .	3-17
Digital Systems . . . . .	3-18
Analog Systems . . . . .	3-18
Spectrum Conservation Factor . . . . .	3-20
SIGNAL PROCESSING . . . . .	3-25
Error Correction/Coding . . . . .	3-26
Adaptive/Transversal Equalizers . . . . .	3-30
Error Correction/Coding And Adaptive Equalizers . . . . .	3-30
TRANSMITTER OUTPUT DEVICES & RF FILTERS . . . . .	3-32
Transmitter Output Device . . . . .	3-32
Klystrons . . . . .	3-32
Traveling-Wave Tubes (TWT) . . . . .	3-33
Gallium Arsenide Field-Effect Transistors ( $G_aA_sFET$ ) . . . . .	3-33
Radio Frequency (RF) Filters . . . . .	3-33
Spectrum Conservation Factor . . . . .	3-34

## TABLE OF CONTENTS

(Continued)

Table	Page
LIST OF TABLES	
3-1 SPECTRUM CONSERVATION DESIGN FACTORS . . . . .	3-2
3-2 HYPOTHETICAL HOP CHARACTERISTICS . . . . .	3-4
3-3 DIGITAL SYSTEM PARAMETERS . . . . .	3-14
3-4 ANALOG SYSTEM PARAMETERS . . . . .	3-16
3-5 MAXIMUM PERMISSIBLE INTERFERENCE LEVELS FOR DIFFERENT MODULATION TYPES . . . . .	3-19
3-6 SPECTRUM CONSERVATION FACTOR FOR ANALOG AND DIGITAL MODULATIONS . . . . .	3-21
3-7 SPECTRUM CONSERVATION FACTOR COMPARISON OF 64- AND 256-QAM FOR SHD ANTENNAS . . . . .	3-22
3-8 SPECTRUM CONSERVATION FACTOR IMPROVEMENT FOR SHROUDED DISH AND CONICAL HORN REFLECTOR ANTENNAS AS A FUNCTION OF MODULATION TYPE . . . . .	3-23
3-9 SPECTRUM CONSERVATION FACTOR FOR ANALOG AND DIGITAL MODULATIONS . . . . .	3-24
3-10 PROCESSING GAIN SUMMARY . . . . .	3-27
3-11 CORRECTION/CODING (64-QAM MODULATION). . . . .	3-29
3-12 SPECTRUM CONSERVATION FACTOR FOR ERROR CORRECTION/CODING (64-QAM MODULATION). . . . .	3-29
EQUALIZER (64-QAM MODULATION) . . . . .	3-27
3-13 SPECTRUM CONSERVATION FACTOR FOR ADAPTIVE EQUALIZER (64-QAM MODULATION) . . . . .	3-31
3-14 SPECTRUM CONSERVATION FACTOR FOR ERROR CORRECTION/CODING AND ADAPTIVE EQUALIZER (64-QAM MODULATION) . . . . .	3-31

TABLE OF CONTENTS  
(Continued)

Figure	Page
LIST OF FIGURES	
3-1 Fixed microwave system antenna types . . . . .	3-5
3-2 Radiation patterns for STD, SHD and CHR antennas . . . . .	3-7
3-3 Denied area as a function of antenna type and transmitter output power for an interference threshold of -101 dBm . . . . .	3-8
3-4 Denied area as a function of antenna type and transmitter output power for an interference threshold of -103 dBm . . . . .	3-10
3-5 Emission spectrum segmentation for evaluation of SCF . . . . .	3-35

LIST OF APPENDICES

Appendix	
A COMPUTER MODEL DESCRIPTION . . . . .	A-1

## SECTION 1 INTRODUCTION

### BACKGROUND

The National Telecommunications and Information Administration (NTIA) is responsible for managing the Federal Government's use of the radio frequency spectrum. NTIA's responsibilities include establishing policies concerning spectrum assignment, allocation and use, and providing the various departments and agencies with guidance to ensure that their conduct of telecommunications activities is consistent with these policies.<sup>1</sup> In discharging these responsibilities, NTIA assesses spectrum utilization, identifies existing and/or potential compatibility problems among the telecommunications systems that belong to various departments and agencies, provides recommendations for resolving any compatibility conflicts that may exist in the use of the frequency spectrum, and recommends changes to promote spectrum efficiency and improve spectrum management procedures.

The radio spectrum is a limited natural resource that must be carefully managed to ensure its availability to accommodate spectrum requirements for new telecommunication systems. Therefore, NTIA has established a long-range plan for management and use of the radio spectrum.<sup>2</sup> One of NTIA's major policy initiatives outlined in the plan is the establishment of procedures to ensure the efficient and effective use of the spectrum. However, because of the economic burden that can be associated with requirements for spectrum efficient communication techniques, NTIA adopts regulatory controls only where necessary to ensure the continued availability of the spectrum. This encourages effective and economical use of the spectrum, development of new technologies in a less restrictive regulatory environment, and the

---

<sup>1</sup> NTIA, Manual of Regulations and Procedures for Federal Radio Frequency Management, National Telecommunications and Information Administration, Washington, D.C., Revised May 1988.

<sup>2</sup> Long-Range Plan for Management and Use of the Radio Spectrum (U), U.S. Department of Commerce, National Telecommunications and Information Administration, Washington, D.C., May 1988.

application of new spectrum conserving technologies only where necessary. In order to accomplish this policy initiative, NTIA has begun:

1. the development of methods to identify heavily used geographical areas in a band,
2. the evaluation of available radiocommunication technologies with respect to their ability to conserve the spectrum.

These two elements will allow NTIA to identify heavily used geographical areas with sufficient lead-time to allow the identification and/or development of appropriate and economical spectrum conservation techniques so that a spectrum crises does not occur and regulatory and policy options are not limited.

Pursuant to element (1) above, NTIA has developed a method for identifying heavily used geographical areas in a band and indices for degree of band use.<sup>3</sup> With respect to spectrum conservation techniques, the Interdepartment Radio Advisory Committee (IRAC) has endorsed a study to identify spectrum conservation techniques for the Fixed Service.<sup>4</sup> This report specifically investigates those techniques applicable to fixed microwave systems.

---

<sup>3</sup> Mayher, R.J.; Haines, R.H.; et al, The Sum Data Base: A New Measure of Spectrum Use, U.S. Department of Commerce, National Telecommunications and Information Administration, TR-88-236, Washington, D.C., August 1988.

<sup>4</sup> MEMORANDUM TO: Deputy Associate Administrator, Office of Spectrum Management; FROM: Executive Secretary IRAC; SUBJECT: Spectrum Resource Assessment of the Federal Government Fixed Service Bands (Above 400 MHz.) NTIA Technical Memorandum 87-127, IRAC Doc. 25498/2.

## OBJECTIVE

The objective of this task was to evaluate spectrum conservation techniques for fixed service point-to-point microwave systems to identify system-design considerations that promote more effective and efficient spectrum use.

## APPROACH

The following approach was taken to accomplish the above objective.

1. Identify major fixed microwave system design factors that conserve spectrum (e.g., antennas, modulation, signal processing, transmitter output device, and RF filters) and the available technology options within each of the major design factors.
2. Establish a microwave reference system to permit the determination of representative systems parameters.
3. Develop a computer model to evaluate spectrum conservation techniques for the fixed microwave systems by applying the definition of spectrum utilization given in the International Radio Consultative Committee (CCIR) Report 662-2.<sup>5</sup>
4. Apply the computer model to determine which major design factors have the most impact on spectrum conservation and to rank available technology options within each of the major design factors.

---

<sup>5</sup> CCIR Report 662-2, "Definition of Spectrum Use and Efficiency," XVIth Plenary Assembly, Vol. 1, Dubrovnik, 1986.

## GENERAL CONCLUSIONS

The following are general conclusions resulting from the study.

1. The spectrum conservation factor (SCF) is a technical concept that can be used to quantitatively assess the spectrum conserving potential of new technologies and to develop new spectrum standards.
2. The spectrum conserving potential of a system is a function of several design factors all of which must be taken into consideration when evaluating the spectrum utilization efficiency of a system. That is one can not say that a system with a particular modulation is more spectrum conserving than a system with another modulation without considering all other design factors such as antennas, signal processing, RF filters, etc.

## SPECIFIC CONCLUSIONS

The following are specific conclusions related to spectrum conservation for each of the major system design factors.

### 1. Antennas

Microwave system antenna characteristics (sidelobe/backlobe levels) have a significant effect on the denial area of a system. For the three types of antennas (dish, shrouded dish and conical horn reflector) considered in the investigation, the following were determined.

- a. The relative improvement in spectrum conservation of the shrouded dish and conical horn reflector antennas over the standard dish antenna is a function of the system modulation. The spectrum conservation improvement is approximately 0 to 150 percent for shrouded dish and approximately 150 to 1500 percent for a conical horn reflector. The greatest improvement occurs for 256-QAM modulation.
- b. Due to the somewhat higher sidelobe levels close to the mainbeam, less than 20 degrees off-axis, for shrouded dish type antennas, there is no appreciable improvement in spectrum conservation for some modulations. However, the low backlobe level characteristics of shrouded dish antennas enhance the accommodation of systems in crowded cosite conditions.

## 2. Modulation

The choice of modulation type used in a microwave system has an effect on the spectrum (occupied bandwidth) and spatial area denied to other users. For the nine types of modulations considered in this investigation, the following were determined.

- a. Single sideband (FDM/SSB) modulation, from a spectrum conserving point of view, is more efficient than the other modulations considered in the analysis for all antenna types.
- b. The higher order digital modulations (modulations with higher transmission efficiency, bits/s/Hz) require higher transmitter output power levels. Therefore, when the CCIR definition of spectrum use and efficiency which takes into consideration denied area is used, modulations which have higher transmission efficiency (bits/s/Hz) may not necessarily be more spectrum conserving. Thus the transmission efficiency (bits/s/Hz) of the digital modulation may not suffice as an indicator of spectrum conservation.
- c. For equivalent systems, with identical signal processing techniques, 64-QAM (Quadrature Amplitude Modulation) is more spectrum conserving (i.e., higher SCF value) than 256-QAM for all antenna types considered.

## 3. Signal Processing

Microwave system signal processing techniques can be used to improve the spectrum conserving properties of a system. For a microwave system using 64-QAM, the following were determined for the digital signal processing techniques considered in the analysis .

- a. The improvement in spectrum conservation due to signal processing techniques is a function of the system antenna type. Microwave systems with dish type antennas obtain the greatest improvement in spectrum conservation when signal processing is used, with the improvement decreasing for systems with shrouded dish and conical horn reflector antennas respectively.
- b. Because of the trade-off between system bandwidth and required carrier-to-noise ratio in error correction/coding techniques, high-efficiency coding techniques (i.e., coding techniques with high coding rates and coding gain) must be used to obtain an improvement in spectrum conservation.
- c. The use of adaptive equalizers can improve the spectrum conservation properties of a system from approximately 25 to 90 percent depending on the type of antenna used.

- d. Some microwave systems use both adaptive equalizers and error correction/coding techniques to improve system performance. The use of both signal processing techniques can improve the spectrum conservation properties of a system from approximately 30 to 170 percent depending on the type of antenna used.

#### 4. RF Filters

The use of transmitter and receiver RF filters greatly enhance the spectrum conserving properties of microwave systems. Their application reduces intermodulation, adjacent channel and receiver spurious response interference.

#### RECOMMENDATIONS

The following are NTIA staff recommendations based on the findings of this report. NTIA management will evaluate these recommendations to determine if they can or should be implemented from a policy, regulatory, or procedural viewpoint. Any action to implement these recommendations will be via separate correspondence modifying established rules, regulations and procedures. The recommendations are as follows.

1. The NTIA in fulfillment of its long-range planning objective of promoting more effective and efficient use of the spectrum, should initiate follow-on tasks to continue the investigation of spectrum conservation techniques for other services.
2. In geographical areas where bands are heavily used, the SCF concept should be for use in the development of spectrum standards which will promote more efficient use of the spectrum.

## SECTION 3

### ANALYSIS OF SPECTRUM CONSERVATION TECHNIQUES

#### INTRODUCTION

This section contains a discussion of the analytical approach used to evaluate spectrum conservation techniques for fixed point-to-point microwave systems. A reference system was used to determine nominal system parameters for the various design factors such as antenna, modulation, signal processing, transmitter output device and RF filters. These nominal system parameters are then used to evaluate the spectrum conservation trade-offs for the various design factors. The relative spectrum utilization efficiency for the various design factors are analyzed as well as the relative spectrum utilization efficiency of the state-of-the-art technologies within each of the major design factors.

The analysis is based on characteristics of microwave systems deployed in the government fixed service band of 7125-8500 MHz. However, the analysis was extended to consider the technology deployed in other point-to-point microwave fixed service bands and current state-of-the-art technology being developed.

#### ANALYSIS APPROACH

To assess the efficiency of the various design factors and technology options, it is necessary to have a quantitative measure of the relative spectrum conservation enhancement properties of that technology. In the past, analysis of spectrum efficiency has dealt primarily with RF bandwidth, transmission efficiency (Bits/second/Hz) or capacity efficiency (Voice channels/Hz).

To utilize the spectrum efficiently, any radiated energy should be kept to a minimum consistent with ensuring an adequate grade of service. This minimization should be effective in the time, frequency, and spacial domains. CCIR Report 662-2 defines spectrum efficiency as the ratio of communications achieved to the spectrum-space used. Spectrum-space is defined as the product of time, bandwidth, and the

spatial volume denied to other users due to potential interference. For this study on analysis of spectrum conservation techniques for the fixed point-to-point systems, the equation in CCIR Report 662-2 was defined as the spectrum conservation factor (SCF) and is given as:

$$SCF = \frac{VC}{T \cdot A \cdot B} \quad (3-1)$$

where:

- VC = Number of voice channels.
- T = Fraction of time a system is used. Defined to be equal to 1 for this analysis.
- A = Denial area (km<sup>2</sup>)
- B = Receiver System Bandwidth (MHz)

The above equation was chosen because it takes into consideration both spectrum and spatial (area) denial in assessing the spectrum conservation enhancement properties of a system. The denial area is the area in which another system can not operate without degradation in system performance below a specified performance criteria. The denial area is a function of the microwave system antenna pattern characteristics, transmitter output power and interference threshold level. APPENDIX A contains a detailed description of the computer program used to evaluate Equation 3-1 and examples of program input and output data.

The relationship between spectrum and spacial (area) denial trade-offs for the various design factors addressed in this section are summarized in TABLE 3-1.

**TABLE 3-1**  
**SPECTRUM CONSERVATION DESIGN FACTORS**

DESIGN FACTORS	TRADE-OFFS
Antenna Modulation Signal Processing Transmitter Output Device RF Filters	Space Spectrum-space Spectrum-space Spectrum Spectrum